Electronic Supplementary Material (ESI) for Catalysis Science & Technology. This journal is © The Royal Society of Chemistry 2016

An oxygen pool from YBaCo₄O₇-based oxides for soot combustion

Guangkai Tian^a, Hui Chen^a, Chenxi Lu^a, Ying Xin^a, Qian Li^a, James A. Anderson^b,

Zhaoliang Zhang^{a*}

^a School of Chemistry and Chemical Engineering, Shandong Provincial Key

Laboratory of Fluorine Chemistry and Chemical Materials, University of Jinan, No.

336, West Road of Nan Xinzhuang, Jinan 250022, P. R. China

^b Surface Chemistry and Catalysis Group, Department of Chemistry, University of

Aberdeen, Aberdeen AB24 3UE, UK

7 pages (including this):

- Table S1
- Figure S1–S4.

Samples	Surface areas	Pore volume	Average pore
	(m ² /g)	(cm^{3}/g)	size (nm)
YBaCo ₄ O ₇	2.3	0.0056	11.6
YBa(Co _{0.85} Al _{0.075} Ga _{0.075}) ₄ O ₇	4.1	0.0241	56.4

Table S1 Textural properties









Figure S1 XRD patterns (a and c) and enlarged XRD patterns (b and d) for YBaCo₄O_{7+ δ} before and after H₂–TPR finished at 350 and 700 °C (a and b) and for YBa(Co_{0.85}Al_{0.075}Ga_{0.075})₄O_{7+ δ} (c and d) before and after H₂–TPR finished at 700 °C.

Figure S2





Co by Al and/or Ga

Figure S3





after O2-TPD at about 900 °C



Figure S4 XRD patterns for YBaCo₄O_{7+ δ} and YBa(Co_{0.85}Al_{0.075}Ga_{0.075})₄O_{7+ δ} after TPO with O₂ at about 650 °C (a) and 880 °C (b)