

Electronic supplementary information

Biocatalytic Janus membranes for CO₂ removal utilizing carbonic anhydrase

Jingwei Hou^a, Chao Ji^{a,b}, Guangxi Dong^{a,c}, Bowen Xiao^a, Yun Ye^a and Vicki Chen^{a,c*}

^aUNESCO Centre for Membrane Science and Technology, School of Chemical Engineering, The University of New South Wales, Sydney, Australia. Email: v.chen@unsw.edu.au; Tel: +61-2-93854813; Fax: +61-2-93855966

^bCooperative Research Centre for Polymers, Notting Hill, VIC 3168, Australia

^cCooperative Research Centre for Greenhouse Gas Technologies (CO₂CRC), School of Chemical Engineering, The University of New South Wales, Sydney, Australia




Figure SI-1. Schematic diagram of the membrane CO₂ hydration system. (1) membrane cell; (2) composite membrane; (3) gas cylinder; (4) gas flow meter; (5) computer; (6) liquid bottle; (7) peristaltic pump.

Table SI-1. Theoretical and actual CNTs loading on the coated membrane

CNTs loading (mg)	Theoretical loading (wt %)	Actual loading (wt %)
5	3.9	3.6 ± 0.4
12.5	9.3	9.5 ± 0.5
25	17.0	16.3 ± 0.8