Reduced Graphene Oxide-β-Cyclodextrin Nanocomposite-based Electrode for Electrochemical detection of Curcumin

Behzad Mirzaei^a, Ali Zarrabi^{a,b*}, Abdollah Noorbakhsh^c, Abbas Amini^{d,e}, Pooyan Makvandi^{f,*}

^a Department of Biotechnology, Faculty of ^{Advanced} Sciences and Technologies,

University of Isfahan, Isfahan, Iran

^b Sabanci University, Nanotechnology Research and Application Center (SUNUM),

Tuzla, 34956 Istanbul, Turkey

^c Department of Nanotechnology Engineering, Faculty of Advanced Sciences and Technologies, University of Isfahan, Isfahan, Iran

^d Centre for Infrastructure Engineering, Western Sydney University, Penrith 2751, NSW, Australia

^e Department of Mechanical Engineering, Australian College of Kuwait, Mishref, Kuwait

^f Chemistry Department, Faculty of Science, Shahid Chamran University of Ahvaz, Ahvaz 6153753843, Iran

*Corresponding authors

E-mails: <u>alizarrabi@sabanciuniv.edu</u> (A. Zarrabi), <u>Pooyanmakvandi@gmail.com</u> (P. Makvandi)

parameter	Code	Level 1	Level 2	Level 3
Electrolyte pH	А	7	8	-
Accumulation time (min)	В	30	45	60
β -CD-rGO concentration (g ml ⁻¹)	С	3	4	5
β-CD to GO ratio	D	0.1	0.25	0.5

Table S-1. Factors and their level values used for Taguchi design.

Run		Response			
	Α	В	С	D	factor
1	1	1	1	1	101
2	1	1	2	2	92
3	1	1	3	3	11
4	1	2	1	1	111
5	1	2	2	2	112
6	1	2	3	3	41
7	1	3	1	2	111
8	1	3	2	3	10
9	1	3	3	1	83
10	2	1	1	3	103
11	2	1	2	1	94
12	2	1	3	2	20
13	2	2	1	2	46
14	2	2	2	3	82
15	2	2	3	1	50
16	2	3	1	3	94
17	2	3	2	1	110
18	2	3	3	2	28

Table S-2. The basic Taguchi L_{18} orthogonal arrays.