

Supplementary information (Revised ESI)

Structural analysis and dye removal behavior of amorphous titania embedded poly(vinyl butyral) hybrid fiber

Anamul Hoque Bhuiyan^{1,2}, Mohammad Zakaria², Koji Nakane^{1,*}

¹ Frontier Fiber Technology and Science, University of Fukui, 3-9-1 Bunkyo, Fukui 910-8507, Japan

² Department of Textile Engineering, Dhaka University of Engineering and Technology, Gazipur-1700, Bangladesh

Email: anamulhb@duet.ac.bd, zakariate@duet.ac.bd

(* For correspondence: Koji Nakane (nakane@matse.u-fukui.ac.jp)




Fig. S1 Schematic principle of as-spun fiber preparation.




Fig. S2 Effect of TTIP bath concentrations on the PVB-amTiO₂F diameters.




Fig. S3 Proposed structural representation of PVB-amTiO₂F as a function of the TTIP bath concentration.




Fig. S4 Variation of the weight loss at (a) 2nd decomposition and (b) 3rd decomposition stage as a function of the TTIP bath concentration.

Table S1 Atomic wt% of the elements (C, O, Ti) observed from EDS analysis

Name of the Fiber	Points	Elements	wt%
10 wt% PVB-amTiO ₂ F	1	C	63.17
		O	27.03
		Ti	8.17
	2	C	23.51
		O	10.19
		Ti	Nil
	3	C	64.67
		O	28.02
		Ti	4.8
50 wt% PVB-amTiO ₂ F	1	C	3.85
		O	8.15
		Ti	49.31
	2	C	Nil
		O	1.32
		Ti	94.33
	3	C	16.11
		O	26.14
		Ti	50.82

Table S2 Effect of TTIP bath concentration on specific surface area of PVB-amTiO₂F fibers

10	15.30
15	14.12
20	16.75
50	12.40




Fig. S5 Determination the pH_{pzc} of PVB-amTiO₂F from the initial pH vs final pH cross-over point.




Fig. S6 Variation of dye absorbance in visible light, where no PVB-amTiO₂F was added.

