Supplementary Information

Study on the definition, mechanism and controllability of secondary bubbles based on the bubble nucleation model in injection foaming polypropylene

Jinfu Xing ^a, Bujin Liu ^a, Tuanhui Jiang ^{a, b}, Yujing You ^a, Xiangbu Zeng ^{a, b}, Jinkui Yang ^{a, b}, Chun Zhang ^b, Wei Gong ^{a,c *}, Li He ^{a, b*}

^a College of Materials and Metallurgy, Guizhou University, Guiyang 550025, China

^bNational Engineering Research Center for Compounding and Modification of Polymeric Materials,

Guiyang 550014, China

° School of Materials and Architectural Engineering, Guizhou Normal University, Guiyang 550025,

China

Correspondence to: L. He (E-mail: lihe@gzu.edu.cn) and W. Gong (E-mail: gw20030501@163.com)



Fig.S1. Visual observation images of secondary bubbles at different melt temperature: (a) MOFIM+200°C, (b) FREEF+200°C, (c) MOFIM+220°C, (d) FREEF+220°C.



Fig.S2. (a and a') Fitting curve of experimental and fitted values under 200°C and 220°C melt temperature.



Fig.S3. (a) and (a') are the N-t curves of experimental and fitted values, (b) the visual video screenshots of spot 1, (c) the visual video screenshots of spot 2



Fig.S4. The screenshot of the visualization video with a mold opening time of 25 s.