SUPPLEMENTARY DATA FOR:

Fabrication of dual anti-corrosive polyaniline microcapsules via Pickering emulsion for active corrosion protection of steel

Weihao Pan^{1#}, Jiahao Dong^{1#}, Taijiang Gui^{2#}, Ren Liu^{*,1}, Xiaoya Liu^{1#}, Jing Luo^{*,1}

1 The Key Laboratory of Synthetic and Biological Colloids, Ministry of Education, School of Chemical and

Material Engineering, Jiangnan University, Lihu Street 1800, Wuxi 214122, China

2 Marine Chemical Research Institute, State Key Laboratory of Marine Coating, Qingdao, Shandong 266071,

China

E-mail: liuren@jiangnan.edu.cn. E-mail: jingluo19801007@126.com.

^{*} Corresponding author. Fax: 86-510-85917763; Tel: 86-510-85917763;




Figure S1. (a) 1H NMR spectrum of PASt copolymer. (b) FTIR spectra and (c) TGA curves of PASt copolymer, pure PANI and PANI particles.




Figure S2. TEM images and digital photos of PASt micelle (a), PANI particles (b). Size distribution of PASt micelle and PANI particles (c).




Figure S3. FTIR spectra (a) and TGA curves (b) of PANI particles.




Figure S4. OM images of Pickering emulsion obtained with different PANI particles as Pickering emulsifiers. (a) PANI_{1.5}, (b) PANI₂, (c) PANI₃, (d) the average droplet diameter of different PANI particles.




Figure S5. OM images of Pickering emulsion obtained with different oil-water ratios. (a) 1.5:1; (b) 1:1; (c) 1:2; (d) 1:3. (the concentration of the PANI emulsifier was 15 mg/mL)




Figure S6. EDS spectrum and corresponding element distribution map of PANI microcapsules.