Supplementary information:

Stability Enhancement and Pronounced Three-photon Absorption in SrCl₂-doped FAPbBr₃ Nano Crystals Sarvani

Jowhar Khanama, Dipanjan Banerjeeb,

Venugopal Rao Somab,*, and Murali Banavoth a,*

 ^a Solar Cells and Photonics Research Laboratory, School of Chemistry, University of Hyderabad, Hyderabad 500046, Telangana, India
 ^bAdvanced Center of Research in High Energy Materials (ACRHEM), DRDO Industry Academia – Centre of Excellence (DIA-COE) University of Hyderabad, Hyderabad 500046, Telangana, India




Figure S1(a-c) Elemental mapping of CI (top panel) and Sr (bottom panel) ions for doped sample from left to right and accordingly labels at the top of each image.




Figure S2(a-d) The calculated microstrain parameters from powder XRD data of each sample; labels are at the top of each sample image, respectively.




Figure S3(a-d) HR-TEM images and SAED pattern (below) patterns for each sample are illustrated from left to right, and labels are at the top of each sample image.





Fig. S4Distribution box plot represents the four samples repeated experimental values of (a) bandgap and (b) PL.



 $\textbf{Fig. S4} \ \textbf{Femtosecond} \ \textbf{Z-scan} \ \textbf{experimental} \ \textbf{schematic}.$




Fig. S5 (a) OA data for toluene (solvent) (b) CA data for toluene. Red lines in both OA and CA data represent the fitted curves, while the open hexagons represent the experimental data.