

SUPPLEMENTARY INFORMATION

Comparative modeling of microwave and ultrasound assisted extraction of phenolics and Berberine from *Coptis teeta* Wall rhizome

Lopamudra Sarma^a, Falguni Patra^b, Pallab Kumar Borah^c, Sunil Meena^d, Raj Kumar Duary^{a,d*}

^a*Department of Food Engineering and Technology, School of Engineering, Tezpur University, Napaam, 784028, India*

^b*Mansinhbhai Institute of Dairy and Food Technology, Dudsagar Dairy, Mehsana, 384002, India*

^c*Heinz Maier-Leibnitz Zentrum, Technical University of Munich, Lichtenbergstraße 1, 85748, Germany*

^d*Department of Dairy Science and Food Technology, Institute of Agricultural Sciences, Banaras Hindu University, Varanasi, 221005, India*

Corresponding author

*Prof. Raj Kumar Duary, E-mail address: rkduary@bhu.ac.in

Table S1: The coded values and corresponding actual values of the optimization parameters used for microwave-assisted extraction

| Independent variable | Coded | Uncoded | Level | | |
|---------------------------|-------|---------|-------|------|------|
| | | | -1 | 0 | 1 |
| Solvent concentration (%) | x_1 | X_1 | 50 | 60 | 70 |
| Time (min) | x_2 | X_2 | 1 | 15 | 30 |
| Microwave Power (W) | x_3 | X_3 | 180 | 540 | 900 |
| Solid-liquid ratio (g/mL) | x_4 | X_4 | 1:10 | 1:25 | 1:40 |

Table S2: The coded values and corresponding actual values of the optimization parameters used for ultrasound-assisted extraction

| Independent variable | Coded | Uncoded | Level | | |
|---------------------------|-------|---------|-------|------|------|
| | | | -1 | 0 | 1 |
| Solvent concentration (%) | x_1 | X_1 | 0 | 50 | 100 |
| Time (min) | x_2 | X_2 | 10 | 45 | 80 |
| Ultrasound Power (W) | x_3 | X_3 | 40 | 120 | 200 |
| Solid-liquid ratio (g/mL) | x_4 | X_4 | 1:10 | 1:45 | 1:80 |