Supporting Information

Development of High Barrier Coated White Cardboard for Fruit Preservation

Zheng Cheng a,b,c,*, Jialin Li a,e, Miao Su a,d, Naiyu Xiao a,b,d,* Le Zhong a,b,*, Xueqin Zhang a,b,c, Meixian Liu a,b, Qifeng Chen c, Jinxian Zhou a,b

^aCollege of Light Industry and Food Technology, Academy of Contemporary Agricultural Engineering Innovations, Zhongkai University of Agriculture and Engineering, Guangzhou, CN 510225, China.

^bGuangdong Provincial Key Laboratory of Lingnan Specialty Food Science and Technology, Zhongkai University of Agriculture and Engineering, Guangzhou, CN 510225, China.

^cState Key Laboratory of Pulp and Paper Engineering, South China University of Technology, Guangzhou, CN 510640, China.

^dResearch Center of Chinese Medicinal Resource Science and Engineering, Guangzhou University of Chinese Medicine, Guangzhou 510006, China.

^eEngineering Research Institute, Jiangxi University of Science and Technology, Ganzhou 341000, China.

*Corresponding author: Dr. Zheng Cheng, E-mail: chengzheng@zhku.edu.cn; Dr. Naiyu Xiao, E-mail: 1308865979@qq.com; Dr. Le Zhong, E-mail: 786583136@qq.com.

Supplementary Results and Discussion




Figure S1. (a) Water vapor permeability of WC respectively coated by paint A or paint B with different coating thicknesses; (b) Gas permeability coefficient of WC respectively coated by paint A or paint B with different thickness.




Figure S2. Chemical structure of PVDC.