Supplementary Information (SI) for RSC Advances. This journal is © The Royal Society of Chemistry 2024

Design of polyurethane composite foam obtained from industrial PET

wastes and MXenes for EMI shielding applications

(supplementary file)

Edina Rusen¹^{**}, Alexandra Mocanu^{1,2†}, Gabriela Toader^{3†}, Aurel Diacon³, Cosmin Romanitan², Ovidiu Iorga⁴, Martino Aldrigo², Catalin Parvulescu², Raul Mitran⁵, Oana Brincoveanu^{2,6} ¹Faculty of Chemical Engineering and Biotechnologies, National University of Science and Technology Politehnica Bucharest, 1-7 Gh. Polizu Street, Bucharest, 011061, Romania ²National Institute for Research and Development in Microtechnologies—IMT Bucharest, 126A Erou Iancu Nicolae Street, 077190 Bucharest, Romania ³Military Technical Academy "Ferdinand I", 39-49 G. Cosbuc Blvd., Bucharest, 050141, Romania ⁴Research and Innovation Center for CBRN Defense and Ecology, 225 Oltenitei Avenue, District 4, Bucharest, Romania ⁵"Ilie Murgulescu" Institute of Physical Chemistry, Romanian Academy, 202 Splaiul Indepedentei, Bucharest, 060021, Romania ⁶Research Institute of the University of Bucharest, ICUB Bucharest, Soseaua Panduri, nr. 90, Sector 5, 050663, Bucharest, Romania [†] Co-authors equally contributed to this study Corresponding authors: Edina Rusen <u>edina_rusen@yahoo.com</u>;





Figure S1. EDX map and elements distribution at 200 and 10 microns (a), and spectrum and element quantification (b) for Sample 0



a)



Figure S2. *EDX map and elements distribution at 200 and 10 microns (a), and spectrum and element quantification (b) for Sample A*



(a)



Figure S3. EDX map and elements distribution at 200 and 10 microns (a), and spectrum and element quantification (b) for Sample B







Figure S4. *EDX map and elements distribution at 200 and 10 microns (a), and spectrum and element quantification (b) for Sample C*