Supporting Information

Surface Crosslinking Effects on Mechanical Properties of Chemically Modified Polymers for Contamination Resistance

Lachlan A. Shaw[†], George Yiapanis[‡], David J. Henry[∥], Shane MacLaughlin[§], Evan Evans[§], Irene Yarovsky^{‡*}

[†] School of Applied Science, RMIT University, Melbourne, Vic, 3001, Australia, GPO Box 2476

[‡] School of Aerospace, Mechanical and Manufacturing Engineering, RMIT University, Melbourne, Vic, 3001, Australia, GPO Box 2476

School of Chemical and Mathematical Sciences, Murdoch University, WA, 6150, Australia

§ BlueScope Steel Research, Port Kembla, Australia

* To whom correspondence should be addressed. Email: Irene.yarovsky@rmit.edu.au.

TABLE CAPTIONS

Table S1: Loading curves for each indentation, including class (Soft, Stiff or Tough). Series abbreviations refer to surface crosslinking type (H – hexamethylene di-isocyanate, I – isophorone di-isocyanate and P – non-surface-crosslinked), functionalization type (F – fluorine, O – hydroxyl) and indented region (A, B, C, D, E).

Figure S1: Percentage distributions of Classes for indentation of unmodified crosslinked surfaces.

Table 1 Loading curves for each indentation, including class (Soft, Stiff or Tough). Series abbreviations refer to surface crosslinking type (H – hexamethylene di-isocyanate, I – isophorone di-isocyanate and P – non-surface-crosslinked), functionalization type (F – fluorine, O – hydroxyl) and indented region (A, B, C, D, E)



Electronic Supplementary Material (ESI) for Soft Matter This journal is C The Royal Society of Chemistry 2013



Electronic Supplementary Material (ESI) for Soft Matter This journal is C The Royal Society of Chemistry 2013



Electronic Supplementary Material (ESI) for Soft Matter This journal is © The Royal Society of Chemistry 2013

